

HDPE FOR HIGH DENSITY POLYETHYLENE PIPE



“305-H” and “306-H” All Stainless Steel Service Saddles

Material Specifications

Shells: Stainless steel per ASTM A 240, type 304, fully passivated ¹.


Bolts: UNC rolled thread, Teflon coated, stainless steel per ASTM A 193, type 304.

Nuts: Stainless steel per ASTM A 194, type 304.

Washers: Flat washers are stainless steel per ASTM A 240, type 304; spring washers are special “spring” grade of stainless steel and plastic lubricating washers.

Gasket: NBR per ASTM D 2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

Tapped Outlet: Stainless steel per ASTM A 240, type 304.



305-H Saddle



306-H Saddle

For above-ground HDPE applications, contact Romac’s Engineering Department at 1-800-426-9341.

Products and prices listed below are standard Romac sizes. For information on other sizes, contact Romac’s Engineering Department.

For important technical information on HDPE pipe, see Page 8-1 & Page 8-2.

“306-H” SADDLE					
NOM. PIPE SIZE	OUTSIDE DIAMETER	TAP	I.P.	C.C.	WEIGHT (lbs.)
2"	2.13 2.38	3/4" & 1"	\$106.74	\$106.74	2 #
3"	3.50	3/4" & 1" 1 1/4" 1 1/2" 2"	204.05 234.38 234.38 234.38	204.05 234.38 234.38 NA	3 #
4"	4.50 4.80	3/4" & 1" 1 1/4" 1 1/2" 2"	209.53 234.38 234.38 234.38	209.53 234.38 234.38 234.38	4 #
5"	5.56	3/4" & 1" 1 1/4" 1 1/2", 2"	219.73 256.74 256.74	219.73 256.74 256.74	4 #
6"	6.63 6.90	3/4" & 1" 1 1/4" 1 1/2", 2"	244.87 262.27 262.27	244.87 262.27 262.27	4 #
8"	8.63 9.05	3/4" & 1" 1 1/4" 1 1/2", 2"	263.81 286.38 286.38	263.81 286.38 286.38	6 #

“305-H” SADDLE					
NOM. PIPE SIZE	OUTSIDE DIAMETER	I.P. OR C.C. 3/4", 1"	I.P. OR C.C. 1 1/4", 1 1/2", 2"	FIP or MIP 2 1/2", 3"	APPROX. WEIGHT (lbs.)
10"	10.75 11.10	\$374.99	\$409.61	\$831.19	14#
12"	12.75 13.20	374.99	409.61	831.19	14 #

¹ **Passivated:** Chemically treated after welding to produce a highly corrosive resistant coating.

To Order: Use pipe O.D. when ordering. Add tap size and thread type. Be specific when ordering. **Indicate if for above ground application.** Tapped outlet products are NO CANCEL/NO RETURN items.

Example: 305-H - 10.75 x 3/4" I.P.

305-H
8" wide with four 5/8" bolts.

- 306-H**
- (A) 2" through 5" nominal sizes with small (3/4" or 1") taps are 6" long with two 1/2" bolts.
 - (B) 6" through 8" sizes with small (3/4" or 1") taps are 6" long with two 5/8" bolts.
 - (C) 3" through 8" sizes with large (1 1/4", 1 1/2", or 2") taps are 8" long with two 5/8" bolts.



The 305-H and 306-H are not to be used on HDPE pipe with an SDR greater than 26.



HDPE Products are No Cancel, No Return Items