



Style CL3 (three section) • Widest Range 1.20"

Material Specifications

Shells: Stainless steel per ASTM A 240, type 304.

Lugs: Ductile iron per ASTM A 536, Grade 65-45-12. Boat-nose fingers designed for ease of installation. Lugs are removeable.

Bolts and Nuts: Trackhead, 5/8" UNC rolled thread, high strength, low alloy, corrosion-resistant steel per AWWA 111. Stainless steel nuts and bolts available on request.

Gaskets: SBR per ASTM D 2000 MAA 610, compounded for water and sewer service. Other compounds available on request.

With
Removeable
Lugs

Meets
AWWA C230



CL3-18.30 x 12" Repair Clamp

Number of Bolts per Clamp Length							
OD Range	7 1/2"	10"	12"	15"	20"	25"	30"
All Ranges	9	12	15	18	24	30	36

O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT						
		7 1/2"	10"	12"	15"	20"	25"	30"
11.04 - 12.24	CL3-12.24 x length	\$312.95	\$366.15	\$456.06	\$545.92	\$723.49	\$907.69	\$1,091.92
12.40 - 13.60	CL3-13.60 x length	30 #	39 #	48 #	58 #	77 #	96 #	115 #
13.14 - 14.34	CL3-14.34 x length	358.61	397.26	493.78	590.34	785.61	980.96	1,176.23
13.45 - 14.65	CL3-14.65 x length	34 #	45 #	56 #	68 #	90 #	112 #	130 #
15.30 - 16.50	CL3-16.50 x length	521.11	713.58	735.23	872.13	1,180.91	1,565.45	1,949.92
17.10 - 18.30	CL3-18.30 x length	36 #	48 #	60 #	72 #	96 #	120 #	144 #
18.00 - 19.20	CL3-19.20 x length	534.82	721.39	776.55	940.43	1,273.42	1,669.05	2,063.85
19.50 - 20.70	CL3-20.70 x length	37 #	50 #	62 #	75 #	99 #	124 #	149 #
21.60 - 22.80	CL3-22.80 x length	592.01	791.27	859.19	973.52	1,318.18	1,777.72	2,236.99
		38#	51 #	64 #	77 #	102 #	128 #	153 #
23.25 - 24.45	CL3-24.45 x length	785.83	1,024.88	1,073.54	1,693.88	2,294.76	2,883.14	3,471.49
		40 #	52 #	66 #	79 #	105 #	132 #	158 #
25.80 - 27.00	CL3-27.00 x length	979.57	1,258.31	1,287.83	1,810.93	2,456.71	3,087.20	3,714.99
		41 #	54 #	68 #	81 #	108 #	136 #	163 #
Add on for 304 stainless steel bolts & nuts		80.74	113.38	145.20	170.16	226.88	283.48	340.20

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes not listed are available on request. Clamps are not to be used for joining plain end pipe.

For Tapped CL3 see Page 1-13.

To Order: Specify catalog number x length of clamp desired.

Example: For a three-section clamp for pipe with an O.D. between 17.10 and 18.30 and clamp length of 12", order **CL3 - 18.30 x 12"**