






Taps for Repair Clamps

SS1, SS2, SS3, SL1, SL2, CL1, CL2, and CL3



SS1-7.00 x 12 x 3/4" IP Tapped Repair Clamp

Available in All Styles



The same design, construction, and installation features as Styles 1, 2, and 3. Tapped outlet is 304 stainless steel, permanently "fused" by GTAW, and fully passivated¹.

To Order:

1. Select size, length, and style of clamp.
2. Select size and type of tapped thread desired from the table below.
3. Add list price for tap to the list price of clamp selected from separate price sheet.
4. **Tapped outlet products are NO CANCEL/NO RETURN items**, please be specific when ordering.

Example: SS1-7.00 x 12 x 3/4" IP would be a one-section clamp for pipe with an O.D. between 6.60 and 7.00, a length of 12" and a 3/4" iron pipe tap size.

ADD-ON LIST PRICES FOR TAPPED CLAMPS

TAP SIZE	TYPE OF THREAD	MINIMUM PIPE O.D.	MINIMUM CLAMP LENGTH	ADD ON LIST PRICE
3/4" or 1"	CC or IP	2.38"	6" for 2.38" through 14.65" pipe O.D. 8" for 14.66" through 19.50" pipe O.D.	54.18
1 1/4"	CC	3.50"	8" for 3.50" through 8.00" pipe O.D. 10" for 8.01" through 14.65" pipe O.D. 12" for 14.66" through 19.50" pipe O.D.	84.93
1 1/4"	IP	2.88"	8" for 2.88" through 8.00" pipe O.D. 10" for 8.01" through 14.65" pipe O.D. 12" for 14.66" through 19.50" pipe O.D.	84.93
1 1/2"	CC or IP	3.50"	8" for 3.50" through 8.00" pipe O.D. 10" for 8.01" through 14.65" pipe O.D. 12" for 14.66" through 19.50" pipe O.D.	84.93
2"	IP	3.50"	8" for 3.50" through 8.00" pipe O.D. 10" for 8.01" through 14.65" pipe O.D. 12" for 14.66" through 19.50" pipe O.D.	84.93
2"	CC	4.50"	8" for 4.50" through 8.00" pipe O.D. 10" for 8.01" through 14.65" pipe O.D. 12" for 14.66" through 19.50" pipe O.D.	103.98
2 1/2" ²	IP or MIP	6.63"	12" for 6.63" through 14.65" pipe O.D. 16" for 14.66" through 19.50" pipe O.D.	240.16
3" ^{2,3}	IP or MIP	6.63"	12" for 6.63" through 14.65" pipe O.D. 16" for 14.66" through 19.50" pipe O.D.	240.16

¹ **Passivated:** Chemically treated after welding to produce a highly corrosion-resistant coating.

² Requires SS2 or SS3

³ 6.63 - 9.99 Taps must be MIP

Tapped CL1 clamps are available in sizes 3.70 and larger.