



Style SS1 (one section) • Normal Range .40"

Material Specifications

Shells and Lugs: Stainless steel per ASTM A 240, type 304.
Bolts: UNC rolled thread, stainless steel per ASTM A 193, type 304.
Nuts: Stainless steel per ASTM A 194, type 304.
Washers: Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.
Gaskets: SBR per ASTM D 2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.

Meets
AWWA C230



SS1-7.00 x 10"
Repair Clamp

Number of Bolts per Clamp Length								
OD Range	6"	8"	10"	12"	16"	20"	24"	30"
2.35 - 9.99	2	2	3	3	4	5	6	8
10.00 - 14.50	2	3	3	4	5	7	8	10

NOM. PIPE SIZE	O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT							
			6"	8"	10"	12"	16"	20"	24"	30"
2" to 2 1/4"	2.35 - 2.63	SS1 - 2.63 x length	\$75.45	\$102.87	\$143.15	\$171.14	\$184.27	\$208.05	N/A	N/A
	2.62 - 2.87	SS1 - 2.87 x length ¹	4 #	4 #	5 #	5 #	8 #	11 #		
2 1/2"	2.75 - 3.00	SS1 - 3.00 x length ¹	78.43	106.94	148.32	175.14	189.76	229.77	N/A	N/A
	2.87 - 3.12	SS1 - 3.12 x length ¹	4 #	4 #	5 #	6 #	8 #	11 #		
3"	3.45 - 3.70	SS1 - 3.70 x length ¹	90.82	112.24	155.11	181.77	205.23	263.31	N/A	N/A
	3.75 - 4.00	SS1 - 4.00 x length ¹	4 #	5 #	5 #	6 #	9 #	12 #		
3 1/2"	3.95 - 4.20	SS1 - 4.20 x length ¹	95.40	120.82	164.13	191.06	213.84	278.21	\$349.41	N/A
			5 #	5 #	6 #	7 #	9 #	13 #	15 #	
4"	4.45 - 4.85	SS1 - 4.85 x length	101.45	126.59	172.49	201.09	223.58	339.09	454.88	\$554.92
	4.74 - 5.14	SS1 - 5.14 x length	5 #	5 #	7 #	8 #	10 #	14 #	16 #	21 #
	4.95 - 5.35	SS1 - 5.35 x length								
	5.20 - 5.60	SS1 - 5.60 x length								
6"	5.95 - 6.35	SS1 - 6.35 x length	126.28	151.49	205.23	241.88	266.77	402.41	506.39	659.30
	6.60 - 7.00	SS1 - 7.00 x length	6 #	7 #	9 #	10 #	14 #	17 #	21 #	26 #
	6.84 - 7.24	SS1 - 7.24 x length								
	7.06 - 7.46	SS1 - 7.46 x length								
8"	7.95 - 8.35	SS1 - 8.35 x length	148.35	177.50	235.12	284.88	325.54	461.18	574.20	757.03
	8.60 - 9.00	SS1 - 9.00 x length	7 #	8 #	11 #	12 #	15 #	19 #	24 #	30 #
	9.00 - 9.40	SS1 - 9.40 x length								
	9.30 - 9.70	SS1 - 9.70 x length								
10"	9.95 - 10.35	SS1-10.35 x length	194.60	236.53	311.17	371.12	426.42	569.38	707.62	968.06
	10.70 - 11.10	SS1-11.10 x length	9 #	11 #	14 #	16 #	24 #	28 #	32 #	42 #
	11.04 - 11.44	SS1-11.44 x length								
	11.40 - 11.80	SS1-11.80 x length								
	11.60 - 12.00	SS1-12.00 x length								
12"	12.10 - 12.50	SS1-12.50 x length	227.15	268.55	356.13	430.10	486.35	675.41	802.16	1,144.94
	12.70 - 13.10	SS1-13.10 x length	11 #	13 #	16 #	18 #	27 #	30 #	36 #	46 #
	13.15 - 13.55	SS1-13.55 x length								
	13.60 - 14.00	SS1-14.00 x length								
14"	14.10 - 14.50	SS1-14.50 x length								

¹ .25" range **For Tapped SS1 see Page 1-13. For Sewer O.D.s see Page 6-7.**

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

To Order: Specify catalog number x length of clamp desired.

Example: For a one-section clamp for pipe with an O.D. between 6.60 and 7.00 and clamp length of 10", order **SS1 - 7.00 x 10"**