



# Style SS2 (two section) • Wider Range .80"

**Material Specifications**

**Shells and Lugs:** Stainless steel per ASTM A 240, type 304.

**Bolts:** UNC rolled thread, stainless steel per ASTM A 193, type 304.

**Nuts:** Stainless steel per ASTM A 194, type 304.

**Washers:** Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.

**Gaskets:** SBR per ASTM D 2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.

Meets  
AWWA C230



SS2-7.64 x 10" Repair Clamp

Number of Bolts per Clamp Length							
OD Range	8"	10"	12"	16"	20"	24"	30"
4.47 - 9.99	4	6	6	8	10	12	16
10.00 - 16.75	6	6	8	10	14	16	20

NOM. PIPE SIZE	O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT						
			8"	10"	12"	16"	20"	24"	30"
4"	4.47 - 5.27	SS2 - 5.27 x length	\$199.74	\$262.35	\$310.68	\$371.42	\$497.39	\$636.14	NA
	4.77 - 5.57	SS2 - 5.57 x length	9 #	12 #	13 #	17 #	25 #	30 #	
	5.20 - 6.00	SS2 - 6.00 x length							
6"	6.57 - 7.37	SS2 - 7.37 x length	229.62	295.40	336.47	434.43	592.99	779.66	\$839.31
	6.84 - 7.64	SS2 - 7.64 x length	11 #	15 #	17 #	22 #	28 #	34 #	43 #
	7.20 - 8.00	SS2 - 8.00 x length							
8"	8.59 - 9.39	SS2 - 9.39 x length	262.82	327.98	382.26	497.39	673.35	890.50	946.69
	8.99 - 9.79	SS2 - 9.79 x length	12 #	17 #	19 #	24 #	30 #	36 #	47 #
	9.20 - 10.00	SS2-10.00 x length							
10"	10.70 - 11.50	SS2-11.50 x length	265.70	430.08	590.30	619.03	825.38	1,097.28	1,236.77
	11.04 - 11.84	SS2-11.84 x length	15 #	18 #	23 #	32 #	41 #	47 #	59 #
	11.40 - 12.20	SS2-12.20 x length							
12"	12.70 - 13.50	SS2-13.50 x length	340.54	493.06	670.19	708.09	955.71	1,218.97	1,392.78
	13.15 - 13.95	SS2-13.95 x length	16 #	19 #	25 #	33 #	41 #	50 #	61 #
	13.50 - 14.30	SS2-14.30 x length							
	13.71 - 14.51	SS2-14.51 x length							
14"	15.00 - 15.80	SS2-15.80 x length	488.23	659.30	851.75	949.40	1,285.56	1,520.78	1,601.19
	15.95 - 16.75	SS2-16.75 x length	18 #	21 #	27 #	33 #	43 #	50 #	64 #

<sup>1</sup> Recommended for use on CL200 ACRB

**For Tapped SS2 see Page 1-13. For Sewer O.D.s see Page 6-8.**

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

**To Order:** Specify catalog number x length of clamp desired.

**Example:** For a two-section clamp for pipe with an O.D. between 6.84 and 7.64 and clamp length of 10" order **SS2 - 7.64 x 10"**