



Style SS3 (three section) • Widest Range 1.20"

Material Specifications

Shells and Lugs: Stainless steel per ASTM A 240, type 304.

Bolts: UNC rolled thread, stainless steel per ASTM A 193, type 304.

Nuts: Stainless steel per ASTM A 194, type 304.

Washers: Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.

Gaskets: SBR per ASTM D 2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.

Meets
AWWA C230



SS3-14.65 x 12" Repair Clamp

Number of Bolts per Clamp Length								
OD Range	8"	10"	12"	16"	20"	24"	30"	36"
All Ranges	9	9	12	15	21	24	30	36

O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT							
		8"	10"	12"	16"	20"	24"	30"	36"
11.04-12.24	SS3-12.24 x length	\$406.40	\$544.15	\$682.91	\$920.85	\$1,323.12	\$1,345.43	\$1,544.30	\$2,244.12
12.40-13.60	SS3-13.60 x length	22 #	27 #	31 #	41 #	53 #	61 #	80 #	94 #
13.14-14.34	SS3-14.34 x length	465.63	604.55	775.29	983.41	1,361.13	1,493.14	1,738.97	2,344.54
13.45-14.65	SS3-14.65 x length	24 #	29 #	33 #	43 #	56 #	65 #	85 #	99 #
15.30-16.50	SS3-16.50 x length	615.06	926.57	954.69	1,238.21	1,645.00	1,721.66	2,532.05	2,883.16
17.10-18.30	SS3-18.30 x length	25 #	30 #	35 #	45 #	59 #	72 #	89 #	103 #
18.00-19.20	SS3-19.20 x length	694.44	948.56	1,008.34	1,262.76	1,712.01	2,116.67	2,680.86	2,974.99
19.50-20.70	SS3-20.70 x length	26 #	32 #	36 #	49 #	63 #	76 #	95 #	112 #
21.60-22.80	SS3-22.80 x length	768.71	1,027.48	1,115.65	1,430.44	1,899.77	2,164.51	2,904.92	3,330.39
		30 #	35 #	40 #	53 #	67 #	80 #	102 #	120 #
23.25-24.45	SS3-24.45 x length	1,020.38	1,132.56	1,258.49	1,832.84	2,469.82	2,832.47	3,576.40	4,302.68
		33 #	38 #	43 #	56 #	71 #	84 #	109 #	129 #
25.80-27.00	SS3-27.00 x length	1,271.90	1,347.30	1,405.41	2,235.05	3,039.63	3,500.06	3,956.27	5,274.99
		35 #	40 #	45 #	60 #	75 #	88 #	115 #	135 #

For Tapped SS3 see Page 1-13. For Sewer O.D.s see Page 6-8.

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

To Order: Specify catalog number x length of clamp desired.

Example: For a three-section clamp for pipe with an O.D. between 13.45 and 14.65 and clamp length of 12", order **SS3 - 14.65 x 12"**