



**ROMAC
INDUSTRIES,
INC.**

1-800-426-9341



"305" All Stainless Steel Service Saddle

Material Specifications

Shells: Stainless steel per ASTM A 240, type 304, fully passivated¹.

Bolts: UNC rolled thread, stainless steel per ASTM A 193, type 304. Fasteners coated to prevent galling.

Nuts: Stainless steel per ASTM A 194, type 304.

Washers: Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.

Gasket: Pad with O-ring gasket. NBR per ASTM D 2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

Tapped Outlet: Stainless steel per ASTM A 240, type 304.

Not recommended for concrete cylinder pipe.



305 Saddle

NOMINAL PIPE SIZE	O.D. PIPE RANGE	8" WIDE		10" WIDE	APPROX. WEIGHT (lbs.)
		I.P. OR C.C. 3/4", 1"	I.P. OR C.C. 1 1/4", 1 1/2", 2"	FIP or MIP 2 1/2", 3"	
10" to 12"	10.00 - 10.80	\$215.84 (4 bolts)	\$246.33 (4 bolts)	\$560.35 (6 bolts)	14 #
	10.80 - 11.60				
	12.00 - 12.80				
	12.80 - 13.60				
	13.70 - 14.50				
14" to 16"	15.00 - 15.80	274.14 (4 bolts)	315.30 (4 bolts)	629.26 (6 bolts)	16 #
	15.90 - 16.70				
	16.70 - 17.50				
16" to 18"	17.30 - 18.10	318.93 (4 bolts)	364.80 (6 bolts)	678.83 (6 bolts)	17 #
	18.15 - 18.95				
	19.00 - 19.80				
18" to 20"	19.30 - 20.10	358.04 (4 bolts)	477.51 (6 bolts)	791.54 (6 bolts)	18 #
	20.00 - 20.80				
	21.10 - 21.90				
22" to 24"	22.00 - 22.80	378.09 (6 bolts)	497.36 (6 bolts)	797.43 (6 bolts)	19 #
	23.20 - 24.00				
	24.60 - 25.40				
	25.70 - 26.50				

¹ **Passivated:** Chemically treated after welding to produce a highly corrosion-resistant coating.

Other ODs available P.O.A.

To Order: Use upper range when ordering. Add tap size. Be specific when ordering. Tapped outlet products are NO CANCEL/NO RETURN items.

Example: 305 - 10.80 x 3/4" I.P.