

ROMAC INDUSTRIES, INC.

STYLE 101NU & 202NU SERVICE SADDLE

SUBMITTAL INFORMATION

MATERIALS

Casting The saddle body is cast from ductile (nodular) iron, meeting or exceeding ASTM A 536, Grade 65-45-12.

Gasket Gasket is made from Nitrile Butadiene Rubber (NBR) compounded for water and sewer service and a tolerance of petroleum products in accordance with ASTM D 2000 MBC 610. Other compounds available for special applications.

U Bolt, Nuts & Washers For sizes 1-1/2" through 3", 1/2" national coarse roll thread, electro-galvanized mild steel strap with heavy hex nuts and 1/2" flat washers. 4" and above uses 5/8" national coarse roll thread, high tensile strength, low alloy steel, with heavy hex nut and 5/8" flat washer, electro-galvanized, meeting AWWA C111 composition specifications. The electro-galvanized coating with chromate seal meet ASTM B633.

Coating Casting is coated with fusion bonded black nylon, 10-12 mils thick, with a dielectric strength of 1,000 v/mil.

PRESSURE RATING Ductile iron, cast iron and steel pipe: rating of pipe up to 350 psi, pipe sizes two inch through 12 inch. For asbestos cement pipe: rating of pipe up to 200 psi maximum. For other applications please consult your representative.

AWWA STANDARDS These service saddles meet the requirements of ANSI/AWWA C800, Underground Service Line Valves and Fittings.

SIZES AND RANGES See Catalog.