

ROMAC INDUSTRIES INC.
STYLE FTS420T (THREADED OUTLET)
SUBMITTAL INFORMATION

Materials

Body	ASTM A 36 Steel Plate.
Tap	NPT or AWWA (CC), male or female threads.
Bolts and Nuts	High strength low alloy steel bolts and nuts. Steel meets AWWA Standard C111. Type 304 and 316 Stainless Steel bolt material optional.
Gaskets	Gaskets are made Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 3 BA715. Other compounds available for petroleum, chemical, or high temperature service.
Coatings	Shop coat applied to parts for corrosion protection in transit. Fusion bonded epoxy in accordance with AWWA C213 optional.

PRESSURE 250 psi 6 inch through 24 inch with up to 8 inch outlets.
200 psi for 28 inch nominal with up to 8 inch outlets.
150 psi 30 inch to 42 inch with up to 8 inch outlets. 100 psi larger than 42 inch with up to 8 inch outlets. Higher pressure ratings can be accommodated. Consult your representative.

AWWA STANDARDS The FTS420T service saddle meet the requirements of ANSI/AWWA C800, Underground Service Line Valves and Fittings.

SIZES AND RANGES: See catalog, for larger sizes consult your representative.